

GREYFIN – Adam Szarafińsk ul. Innowacyjna 1 lok.111 16-400 Suwałki / Polska Tel. +48 660 420 773 www.greyfin.pl

VARI-FEED WICK OILERS



Vari-Feed wick oilers are used to provide a controlled amount of oil to a bearing or other machinery part. The principle of delivery combines gravity feed with capillary action in the wick to provide a constant feed rate of oil regardless of the fill level in the reservoir. Feed rate is determined by the viscosity of the oil and the type of wick being used.

Two styles of operation are available depending on the application. When continuous delivery is required the N or NS models are used.

For on-off control of the oiler, the NA and NAS models have a filler cap with gasket that stops oil delivery when fully closed. By turning the fill cap slightly, the threaded air vent is opened allowing oil to flow.

FEATURES

- Feed rate is constant and adjustable only by changing to a different wick
- 5 wick speeds are available and color coded for easy replacement or installation. A multi-pack of different wick speeds is included with each oiler
- Dust proof caps supplied with N and NS models. NA and NAS models have sealed cap and operate only when cap is in vent position
- Plastic reservoirs have reinforcing ribs for long life
- Oil sights available on NS and NAS models for visual indication of oil flow
- Copper brazing of all steel connections provides long life and leak proof design
- Zinc plating resists corrosion

SPECIFICATIONS

Max. Operating Temp.	165°F Continuous
Reservoir	Butyrate Plastic
Oil Sight	Acrylic
Sight Gaskets	Buna-N
Wicking	Wire Cored Cotton
Material	Steel and Brass
Finish	Bright Zinc Plated

SELECTION CHART—N, NS

Model No.		Compain	Connection	Dimensions (in.)	
Type N	Type NS	Capacity	(NPT)	Α	В
30742	30842	4 oz.	1/4	2-5/16	3
30782	_	8 oz.	1/4	2-5/8	4

SELECTION CHART—NA, NAS

Model No.			Connection	Dimensions (in.)	
Type NA	Type NAS	Capacity	(NPT)	A	В
30942	31042	4 oz.	1/4	2-5/16	3-1/4
_	31082	8 oz.	1/4	2-5/8	4-5/16

REPLACEMENT WICKS

Packed 50 of one color per carton. Also sold by the foot.

ş <u>.</u>	Model No.	Length	Description	Thickness
1	30701		White - Very Fast Feed Wick	3 mm
	30702	1-3/8"	Green/White - Fast Feed Wick	5 mm
	30703		White/Blue - Medium Feed Wick	6 mm
	30704		Red/White - Slow Feed Wick	8 mm
	30705*		White/Blue -Very Slow Feed Wick	12 mm

^{*}Contains 100 pieces of white/blue wicks



